



Technology Done **Better.**

SmartSource[®] Adaptive



Standard Length



Small Form Factor

SmartSource Adaptive

The SmartSource Adaptive is the most flexible MICR-enabled imaging solution available. It is capable of scanning a wide variety of intermixed document types up to Legal-size (8.5 x 14.2 inches), enabling you to reduce expenses by integrating a single device that can handle all of your document imaging needs. Based on the successful SmartSource check imaging platform, the Adaptive incorporates many of the proven features first introduced on the Professional and Expert models.

Ease of Operation

The new open feeder reduces document preparation requirements and enables one-handed loading of documents by automatically opening when empty. The SmartSource Adaptive can be configured to start feeding automatically when documents are loaded into the feeder, with the touch of a button, or through software control. In case of a document jam, the SmartClear button eliminates the need to open or remove covers to retrieve the document.

Low Operator Maintenance

The SmartSource Adaptive is engineered to process high volumes of daily items, yet it requires minimal maintenance. When needed, cleaning is easy. Often, all that is required is a rapid cleaning procedure which uses a cleaning card and does not require opening or removing any covers. The optional ink-jet endorser uses a custom ink formulation which eliminates the need for operators to clean the cartridge.

Standard Features

The SmartSource Adaptive is a perfect fit in any PC-based environment. Its extensive set of features offers unparalleled flexibility. Standard features include an auto-feeder with an open feeder design for improved productivity, industry-leading Magnetic Ink Character Recognition (MICR) reader, high-quality image with 300 dpi image cameras, and endorsement decisions based on MICR and/or front image content such as optical character recognition, bar code recognition, or image quality results.

Optional Features

Optional features include Optical Character Recognition (OCR), a front franking stamp, and a 4-line graphics-capable rear ink-jet endorser. The 4-line rear ink-jet endorser supports any Microsoft true-type font and eliminates the need for a separate receipt/validation printer. In addition to endorsing customer-deposited checks, the SmartSource printer is capable of validating internal cash tickets and an array of teller documents including customized customer deposit receipts, envelopes, and even official checks.

Small Form Factor Option

The SmartSource Adaptive is available in a small form factor model for operating environments with limited desktop space.

SmartSource Adaptive Technical Information

Document Processing Throughput	Product Dimensions
Page: 30 dpm Check: 70 dpm (40-50 dpm when scanning legal-size documents)	Standard Length: 20.2 in (51.3 cm) Small Form Factor Length: 15.6 in (39.7 cm) Height: 11.3 in (28.8 cm) Depth: 6.4 in (16.2 cm)
Power Requirements	Document Hopper
100-240 VAC @ 50/60 Hz	30 to 100 item hopper capacity - 30 page-size items - 100 check-size items
Weight	Document Feeder
Installed weight: 9.7 lbs. (4.4 kg) Power supply: 0.75 lbs. (0.34 kg)	Automatic document feeder Double document detection
Certifications	Magnetic Ink Character Recognition (MICR)
CE, UL/TUV, CSA, RoHS, VCCI, FCC Class A	E13B and CMC7 read with auto-detect
Document Sizes	Image Capture
Document size - Height (min./max.): 2.00 to 8.5 inches (5.08 to 21.59 cm) - Length (min./max.): 2.90 to 14.2 inches (7.37 to 36.07 cm) Document weight - Paper weight, nominal: 20 lb (75 gr/m ²) to 24 lb (90 gr/m ²) Document Height-to-Length ratio - Minimum aspect ratio: 1.50 Document Thickness - 0.004 inches (0.1 mm) to 0.006 inches (0.15 mm)	Front and rear image capture at 300 dots per inch (dpi) Image renditions available - up to (5) bi-tonal and gray images Image resolutions available - 300, 240 or 200 dpi (bi-tonal (black / white)) - 300, 240, 200, 150, 120 or 100 dpi gray level (256 gray shades)
Communication Interface	Image Compression Standards
USB 2.0 high-speed	CCITT Group 4 (bi-tonal images) JPEG Baseline (gray level images)
Operating Systems	Optical Character Recognition (OCR)
Windows XP Professional 32-bit Windows VISTA Business 32 and 64-bit Windows 7 Professional 32 and 64-bit	OCR-A, OCR-B and E13B fonts supported Two (2) 0.50 inch OCR scan bands provided 96 characters per scan band MICR/OCR combine read
Operator Interface	Endorsement
Power switch Combined Feeder Start/Stop and SmartClear Button Light Emitting Diode (LED) - Three (3) LED status lights	Front Franker - Franking roller with fixed message - Franking actuation, controlled programmatically Rear Endorser - Ink jet print cartridge (600 dpi) - One (1) to four (4) line endorsement, any True Type font - Two (2) vertical endorsement locations, manually selected by operator allows eight (8) single-line vertical endorsement locations - Graphics capable for logos and signatures - Three (3) levels of print quality (economy, standard, or premium) - Programmatically controllable based on MICR, OCR, and/or Image Quality results
Application Programming Interfaces (API)	Output Pockets
CAPI (Common Application Programming Interface) Device Suite Professional PC version Ranger® for SmartSource Twain	Single 100 item capacity pocket

NOTE: Not every API Operating System combination may be qualified. Contact your application provider for more information.

For more information about the entire line of Burroughs remote capture products, call 1-800-BURROUGHS (1-800-287-7684) or visit www.burroughs.com

Burroughs is a registered trademark licensed to Burroughs, Inc. in the United States and other countries. SmartSource, ReceiptNOW and Cache2Cash are registered trademarks of Burroughs, Inc. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.



SmartTIP Use your smartphone for more information.